

**MOTOR GUARD HI-TEMP REFRIGERATED DRYERS**

<b>Model No.</b>		<b>RF-2049</b>	<b>RF-3050</b>	<b>RF-2051</b>	<b>RF-2052</b>	<b>RF-2053</b>
<b>Specifications</b>						
Nominal Airflow Rating	SCFM	20	35	50	75	100
Outlet Pressure Dew Point	° F	50	50	50	50	50
Compressor Rating	HP	5	10	15	20	25
Electrical Rating	V/PH/Hz	115/1/60	115/1/60	115/1/60	115/1/60	115/1/60
Input Power	KW	0.73	0.73	1.37	1.37	2.11
Rated Inlet Air Temperature	° F	180	180	180	180	180
Maximum Air Inlet Temperature	° F	180	180	180	180	180
Rated Air Inlet Pressure	PSIG	100	100	100	100	100
Maximum Air Inlet Pressure	PSIG	250	250	250	250	250
<b>Physical Data</b>						
Length	In	13	13	17	17	17
Width	In	10	10	17	17	17
Height	In	28	28	37	37	46
Shipping Weight	Lbs	79	81	150	155	170
Pipe Connection	NPT	1/2	1/2	3/4	3/4	3/4
<b>Features</b>						
Compressor Type	Reciprocating					
Refrigerant	R407c					
Condensator Type	Fan/Coil Condensator					
Condensate Drain Type	Air Operated Float Drain					
Specifications are subject to change						